



F-1000 Mud pump parts

	F-1000 Mud pump parts	BOMCO		
	Fluid End			
2	Valve Assy., including 1 PC of valve body assy. AH000002-010200, 1 PC of valve rubber AH000002-010205, 1 PC of valve seat AH000002-0101	AH0000020100	each	180
3	Valve rubber	AH000002010205	each	200
4	Valve spring	AH33001-05.16	each	180
5	Liner seal	AH1001010504	each	120
6	Valve seal	AH1001010508	each	200
7	Valve guide, Upper	AH1001010510	each	60
8	Valve guide, Lower	AH10010101052200	each	100
9	Spring Guide	AH33001-05.13.00	each	100
10	Valve Guide Retainer	AH33001-05.14	each	80
11	Valve Spring	AH33001-05.16	each	150
12	Valve pot cover	AH1001010509	each	70
13	Double-lip seal 4.5"x5.5"x0.5"	AH1001010416	each	50
14	Liner 5-1/2"	AH33001-05.22C.00	each	24
15	Liner 6"	AH33001-05.22C.00	each	30
16	Liner 6-1/4"	AH33001-05.22C.00	each	30
17	liner 6-1/2"	AH33001-05.22C.00	each	30
18	Piston 5-1/2" (Containing polyurethane rubber)	AH33001-05.19A.00	each	72
19	Piston 6" (Containing polyurethane rubber)	AH33001-05.19A.00	each	90
20	Piston 6-1/4" (Containing polyurethane rubber)	AH33001-05.19A.00	each	90
21	Piston 6-1/2" (Containing polyurethane rubber)	AH33001-05.19A.00	each	90
22	Piston rod clamp	AH33009-05.02.00	each	9
23	Piston rod	AH33001-05.21	each	6

24	Piston nut M39x3	AH33001-05.18.00	each	12
25	O ring 41.2×3.55	530301010412036000	each	200
26	Clamp Assy	AH100102-050500	each	8
27	Sealing ring	AH1001010404	each	50
28	O-ring 175×3.55	530301011750036000	each	200
29	O-ring 140×7	530301011400070000	each	200
30	O-ring 97.5×3.55	530301010975036000	each	200
31	O-ring 185×7	530301011850070000	each	200
32	O-ring 115×5.3	530301011150053000	each	200
33	O-ring 165×7	530301011650070000	each	200
34	O-ring 200×8.6	AH10010120605	each	100
35	O-ring 80×5.7	AH100101210607	each	100
36	Retainer ring 80x70x2	AH100101210606	each	100
37	Retainer ring 200x185x2.5	AH100101210604	each	100
38	Oil seal 8.5"x10.5"x0.625"	AH1001010311	each	90
39	Pony rod	AH1001010407	each	6
40	Gear oil pump, 2S	512601010031000000	each	2
41	V-belt, A3150	140301012031500000	each	10
42	V-belt, 5ZV25J-8000	140302025408000000	each	10
43	O-ring 175×3.55	530301011750036000	each	200
44	O-ring 140×7	530301011400070000	each	200
45	O-ring 97.5×3.55	530301010975036000	each	200
46	O-ring 185×7	530301011850070000	each	200
47	O-ring 115×5.3	530301011150053000	each	200
48	O-ring 165×7	530301011650070000	each	200
49	Oil seal 8.5"x10.5"x0.625"	AH1001010311	each	90
	Ring Gasket			
50	Ring gasket R-24	T508-5004	each	10
51	Ring gasket R-27	T508-5003	each	10
51	Ring gasket R-35	T508-5005	each	10
52	Ring gasket R-39	T508-5001	each	10
52	Ring gasket R-44	T508-5002	each	10
53	Fluid End Studded Assy	AH34007-05.01.00	set	1
53	Thread Ring	AH33001-05.02	each	1
54	Cylinder Head	AH33001-05.03A	each	6
54	Cylinder Head Plug	AH33001-05.05	each	6
55	Liner Cage	AH33001-05.06	each	1
55	Stud	T50-4010	each	50

56	Nut	T51-2002	each	50
56	Locking Clip	AH33001-05.30	each	1
57	Double Lip Seal 4.5"x5.5"x0.5"	AH34001-04.23	each	1
57	LUBRICATION ASSEMBLY	AH33009-06.00	set	1
58	PISTON & LINER WASH	AH33009-08.00	each	1
58	Pump	AH36001-08B.11.00	each	2
59	Cylinder Head Plug Tool	AH36001-17.02A	each	1
	Lifting Tool			-
60	Seat Lifting Tool	AH33001-31.09.01	each	1
61	Charging Hose	AH33001-31.10.00A	each	1
62	Manual Hydraulic Pump 70MPa	PSH-II	each	1
63	Sealing Ring 39	T508-5001	each	5
	Pulsation Dampener			
64	Bottom Plug	AH33002-02	each	5
65	Bladder	AH33002-03.00	each	5
66	Pressure Gauge 0-25MPa	Y-60	each	4
67	Needle Valve 1/4"	JZR3-L8	each	4
68	Sealing Washer	T514-1001	each	10
69	Adapter Bushing	AH33003-01	each	2
70	Plain Washer	AH33003-02	each	20
	Shear Relief Valve			
71	Plunger Seal	AH33003-03.00	each	50
72	Body	AH33003-04	each	2
73	Plunger Stem	AH33003-05	each	5
74	Bumper	AH33003-06	each	20
75	Roll Pin	AH33003-07	each	20
76	Shear Bar	AH33003-10	each	10
77	Shear Pin	AH33003-11	each	100
79	Swivels, model XSL170, details please refers to attached specification.		each	1
80	Upper Kelly cock, working pressure: 10000PSI, Max. OD: 5-3/4", Min. ID:3" , Connection : 4-1/2" Reg LH, details please refers to attached specification		each	2
81	Lower Kelly cock, working pressure: 10000PSI, Max. OD: 6-5/8" , Min. ID:2-1/4" ,		each	2

	Connection: NC50, details please refers to attached specification			
82	Lower Kelly cock, working pressure: 10000PSI, Max. OD: 4-3/4" , Min. ID:2-1/4" , Connection : NC38, details please refers to attached specification		each	2
83	Kelly Save sub Pin, 4-1/2" IF PIN X 4-1/2" IF BOX, details please refers to attached specification		each	3
84	Kelly Save sub Pin, 3-1/2" IF PIN X 4-1/2" IF BOX, details please refers to attached specification		each	3
85	Cross over, 4-1/2" REG LH BOX X 6-5/8" REG LH PIN, details please refers to attached specification		each	2
	Other			
86	Rotary hose , W/hammer union type 1002, Max. working pressure: 5000PSI, Bore size: 4" , Length: 17 m, details please refers to attached specification		each	2
87	Screw, M6x25, C/w 1 PC of nut and 1 PC of gasket, used to fasten side/cross support		each	600
88	Butterfly valve 6"	GK001200	each	30